

PRESSURE PVC PIPE

For Aircon Drain - 16mm, 20mm, 25mm, 32mm



PRESSURE PVC PIPE

Composed of high grade materials. Rated to PN12 (Class 12). Commonly used in HVAC applications for condensor drains.

TECHNICAL DATA

15 PN 18 PRESSURE 6 MTR		
DIMENSIONS	MIN (mm)	MAX (mm)
Pipe Wall Thickness	1.6	2.0
Ovality	21.1	21.6
Mean Diameter	21.2	21.5
Effective Length	6000	6010
Socket Length	35	38
Pack Size	1045 Lengths	
Pressure Rating	PN 18	

20 PN 12 PRESSURE 6 MTR		
DIMENSIONS	MIN (mm)	MAX (mm)
Pipe Wall Thickness	1.4	1.7
Ovality	26.5	27.0
Mean Diameter	26.6	26.9
Effective Length	6000	6010
Socket Length	35	40
Pack Size	770 Lengths	-
Pressure Rating	PN 12	

25 PN 12 PRESSURE 6 MTR		
DIMENSIONS	MIN (mm)	MAX (mm)
Pipe Wall Thickness	1.7	2.1
Ovality	33.3	33.8
Mean Diameter	33.4	33.7
Effective Length	6000	6010
Socket Length	38	40
Pack Size	540 Lengths	5 Per Bundle
Pressure Rating	PN 12	

32 PN 12 PRESSURE 6 MTR		
DIMENSIONS	MIN (mm)	MAX (mm)
Pipe Wall Thickness	2.2	2.6
Ovality	42.0	42.5
Mean Diameter	42.1	42.4
Effective Length	6000	6010
Socket Length	35	40
Pack Size	300 Lengths	5 Per Bundle
Pressure Rating	PN 12	

AS/NZS 1477