


Vibrabase

Universal Flat Roof Support System Easy to install, no penetration



KEY FEATURES

- Recycled SBR from truck tyres.
- Compatible with Unistrut systems.
- Robust and weighted product to reduce product movement on roof.
- Pre galvanised channel.
- Practical and versatile 6-feet range for pipe work and cable trays.
- For smaller outdoor condensing units or air source heat pump installations.
- Vibration and noise absorption.

TECHNICAL DATA

Description	Model	Length	Width	Height	Max Load	Qty
Rubber Feet Inc Channel 250	SFR 250	250 MM	180 MM	95 MM	160 KG	1
Rubber Feet Inc Channel 400	SFR 400	400 MM	180 MM	95 MM	240 KG	1
Rubber Feet Inc Channel 600	SFR 600	600 MM	180 MM	95 MM	450 KG	1
Rubber Feet Inc Channel 1000	SFR 1000	1000 MM	180 MM	95 MM	645 KG	1
Rubber Feet Inc Channel	SFR 250 Low	250 MM	130 MM	50 MM	160 KG	1
Rubber Feet Inc Channel	SFR 400 Low	400 MM	130 MM	50 MM	240 KG	1
Rubber Feet Inc Channel High Block 600	SFR 600 High Block	600 MM	130 MM	150 MM	450 KG	1
Rubber Feet Inc Channel High Block 1200	SFR 1200 High Block	1200 MM	130 MM	150 MM	645 KG	1

