

# POWA Group

## Glove Arax Touch

*Polyurethane Dipped Cut 3 Resistant*



# GLOVE ARAX TOUCH

## Polyurethane Dipped Cut 3 Resistant

### FEATURES & BENEFITS

- EN388:2016 Cut Resistance Level "C".
- ASTM Cut Level 3.
- Contact heat resistant to 100°C.
- Good cut resistance without sacrificing comfort or dexterity.
- Water based polyurethane finish coated palm.
- Breathable Arax® liner.
- Form fitting for comfortable all day wear.
- Colour coded cuff for size identification.

### APPLICATIONS

Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling, Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Cut & Abrasion Risks

### PRODUCT DETAILS

Material: Engineered Composite 15 Gauge Seamless Arax® Liner  
Dip: Water based PU in Black  
Cuff Type: Knitted  
Colour: Blue Speckle  
Available Sizes: 8, 9, 10  
Qty/Pack: 12 pairs  
Qty/Carton: 120 pairs

### STANDARDS

CE CATEGORY:  
II Intermediary risk in accordance with:  
EN 420 /AS / NZS2161.2:2005 General Requirements  
EN 388:2016 Protection Against Mechanical Risks  
Results - 4X42C  
EN 407 /AS / NZS2161.4:1999 Protection Against Thermal Risks (Heat & Fire)  
Results - X1XXXX  
ASTM F1 790 Cut Level  
Results - 3



### PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
8	9.5cm +/-	22.5cm +/-
9	10.0cm +/-	23.5cm +/-
10	10.5cm +/-	24.5cm +/-

### CUT TEST - ISO13997

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
A	<2	200gms
B	≥5	500gms
C	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg