

POW^AGroup

Replacement Pads - Suit Headband Earplugs

Hearing protection for noise levels to 105dB(A)



REPLACEMENT PADS - SUIT HEADBAND EARPLUGS

Hearing protection for noise levels to 105dB(A)

FEATURES & BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 4 $SLC_{80}24dB$.
- Hearing protection for noise levels to 105dB(A).
- Coloured blue for food safety.
- Disposable, PU foam pads.
- Disposable PU foam pads are ergonomically designed to fit the ear for maximum protection.
- Pairs individually packaged.



APPLICATIONS

Agriculture, Construction, Fire Protection, Food Services, Forestry, Government, Emergency Services, Manufacturing, Medical, Military, Councils, Mining, Oil and Gas, Pharmaceutical, Steel and Metals, Transportation, Welding, Logistics and Transport, Automotive & Utilities.

PRODUCT DETAILS

Material: PU Foam
Colour: Blue Foam
Size: Standard One Size

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 4 $SLC_{80}24dB$.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 105dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



COMFORT



HI-VIS



HYGIENIC



REUSABLE

MAINTENANCE

Before handling any earplugs, ensure hands are clean. Always check your earplugs and discard if damaged, worn or dirty. Silicone plugs can be washed if necessary. Single use ear plugs can cause health issues if used when dirty.

If kept clean and undamaged, silicone (reusable) ear plugs can be used many times over. Clean with mild soap/water and store in a case away from extreme heat and direct sunlight when not in use. On banded earplugs, clean and replace pads regularly as required.

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	24.2	23.9	22.7	25.3	31.3	41.8	41.5
Standard Deviation	3.3	3.7	4.9	4.1	5.8	4.4	5.4
Mean-Minus-Standard Deviation Attenuations	20.9	20.2	17.8	21.2	25.5	37.4	36.1

SLC_{80} Value is 24 (Class 4)