

POW**A**Group

Ear Plug Uncorded - Foam (200 Pack)

Hearing protection for noise levels to 110dB(A)



EAR PLUG UNCORDED - FOAM (200 PACK)

Hearing protection for noise levels to 110dB(A)

FEATURES & BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 $SLC_{80}27dB$.
- Hearing protection for noise levels to 110dB(A).
- Hi-vis yellow for visual identification & compliance.
- Economical & convenient choice for work situations that demand a high degree of comfort, frequent changes or where hygiene presents a problem for re-usage.
- Bell shape provides maximum comfort.
- Design makes it easier to insert & reduces tendency to back out of the ear.
- Pairs packaged in individual poly bags.

APPLICATIONS

Agriculture, Construction, Fire Protection, Food Services, Forestry, Government, Emergency Services, Manufacturing, Medical, Military, Councils, Mining, Oil and Gas, Pharmaceutical, Steel and Metals, Transportation, Welding, Logistics and Transport, Automotive & Utilities.

PRODUCT DETAILS

Material: PU Foam
Length: 2.5cm
Diameter: 1.6cm
Colour: Hi-Vis Yellow Foam

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 $SLC_{80}27dB$.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



COMFORT



HI-VIS



HYGIENIC

MAINTENANCE

Before handling any earplugs, ensure hands are clean. Always check your earplugs and discard if damaged, worn or dirty. Silicone plugs can be washed if necessary. Single use ear plugs can cause health issues if used when dirty.

If kept clean and undamaged, silicone (reusable) ear plugs can be used many times over. Clean with mild soap/water and store in a case away from extreme heat and direct sunlight when not in use. On banded earplugs, clean and replace pads regularly as required.

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	22.9	25.5	29.8	30.0	32.4	40.1	40.1
Standard Deviation	6.5	6.3	7.0	6.8	4.9	6.6	7.0
Mean-Minus-Standard Deviation Attenuations	16.4	19.2	22.8	23.2	27.5	33.5	33.1

SLC_{80} Value is 27 (Class 5)