

POWAGroup

Replacement Filter Cartridges

For 1431-HMPTM (PCABEK1)



REPLACEMENT FILTER CARTRIDGES

For 1431-HMPTM (PCABEK1)



FEATURES & BENEFITS

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- For use on the ProChoice Maxi Mask 2000TM Half Mask Respirator.
- Twin filter design provides a more balanced fit, lower breathing resistance & improves field of vision.
- ABEK1 filters protect against a wide range of chemicals including organic vapour, acid gas, sulphur & ammonia.
- Can be fitted with the P2 ProChoice filter pads to provide extra protection against dust/mist particles.
- Easy 'lock-on' system.
- Comes complete with 1 pair of ABEK1 ProChoice filters.



GAS/VAPOUR
PROTECTION



REUSABLE



VALUE

PRODUCT DETAILS

Weight: 110g per filter

APPLICATIONS

Ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, manufacturing, metal processing, mining and quarrying, transportation.

STANDARDS

CERTIFIED TO:
AS/NZS 1716:2012 Respiratory Protective Devices
Certified by SAI Global

To be used in conjunction with: AS/NZS 1715:2009 -
Selection, use & maintenance of respiratory protective
equipment

WARNINGS & USE LIMITATIONS

1. Facial hair has the potential to compromise the required protective seal of the respirator.
2. Ensure adequate oxygen levels are present.
3. Ensure the contamination is known and the respirator is suitable for the application.
4. Replace when taste, smell or the breathing resistance is high.
5. Store in a clean resealable storage device.

CLASSIFICATION	EFFICIENCY	EXAMPLES OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

CARE INSTRUCTIONS

Shelf life of the unopened product is 3 years from date of manufacture when stored within temperature range of -20°C to +25°C & less than 80% relative humidity.

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

Ensure mask is correctly fitted prior to each use & conduct annual fit testing in accordance with AS/NZS 1715:2009.